



Federal Democratic Republic of Ethiopia

👉 EDICT OF GOVERNMENT 👈

In order to promote public education and public safety, equal justice for all, a better informed citizenry, the rule of law, world trade and world peace, this legal document is hereby made available on a noncommercial basis, as it is the right of all humans to know and speak the laws that govern them.

ET ISO 28198 (2012) (English):
Vegetable fats and oils -- Determination
of toluene insoluble matter

ISO INSIDE



BLANK PAGE



**ETHIOPIAN
STANDARD**

ES ISO 28198:2012

First edition

**Vegetable fats and oils---Determonation
of toluene insoluble mattter
(Identical with ISO 28198:2009)**

ICS: 67.200.10

Published by Ethiopian Standards Agency
©ESA



Foreword

This Ethiopian Standard has been prepared under the direction of the Technical Committee for Animal and vegetables fats and oils (TC 23) and published by the Ethiopian Standards Agency (ESA).

The standard is identical with ISO 28198 :2009 ,Vegetable fats and oils - Determination of toluene insoluble matter, published by International Organization for Standardization (ISO).

For the purpose of this Ethiopian Standard, the adopted text shall be modified as follows.

- The phrase “International Standard” shall be read as “Ethiopian Standard”; and
- A full stop (.) shall substitute comma (,) as decimal marker.

Vegetable fats and oils — Determination of toluene insoluble matter

1 Scope

This International Standard specifies a method for the determination of the content of toluene insoluble matter (TIM) in lecithin formulations, which indicates the presence of impurities such as protein, carbohydrate-containing extraction residues and other solid contaminants. This method is applicable to all types of vegetable lecithin.

The purpose of the method is to enable the analysis of lecithin under several regulations. Lecithin [Codex International Numbering System for Food Additives (INS) No. 322] is a generally permitted additive and the determination of the TIM is part of many specifications. The purity requirement with regard to TIM content is based on the method specified.

Toluene is the replacement for the carcinogenic benzene, which was used in older methods.

2 Terms and definitions

For the purposes of this International Standard, the following terms and definitions apply.

2.1

toluene insoluble matter

TIM

w_{TIM}

quantity of those substances that are insoluble in toluene under the conditions specified in this International Standard

NOTE The toluene insoluble matter content is expressed as a mass fraction in grams per 100 g.

3 Principle

The sample is dissolved in toluene and filtered through a glass filter crucible of defined pore size (P 40). The insoluble residue is dried at $(103 \pm 2) ^\circ\text{C}$ and weighed.

Glass filter crucibles with other pore sizes give different results and shall not be used.

4 Reagents

WARNING — Attention is drawn to the regulations which specify the handling of hazardous substances. Technical, organizational and personal safety measures shall be followed.

During the analysis, unless otherwise stated, use only reagents of recognized analytical grade and distilled or demineralized water or water of equivalent purity.

4.1 Toluene.

5 Apparatus

5.1 Glass filter crucible P 40¹⁾, capacity 30 ml, pore size 16 µm to 40 µm.

NOTE For the determination of TIM, the Joint FAO/WHO Expert Committee on Food Additives (JECFA) recommends the use of a filter funnel G3 with a porosity of 16 µm to 40 µm (see Reference [5]). According to ISO 4793^[1], the porosity G3 (G2) is denominated as P 40 (P 100).

IMPORTANT — To clean glass filter crucibles, fill the ultrasonic bath with a phosphate-free alkaline cleaning solution²⁾ for laboratory glassware with a volume fraction of 10 %. Put the glass filter crucibles into the ultrasonic bath for 30 min. Wash the glass filter crucibles with water, and if necessary repeat the cleaning step. Clean the glass filter crucibles in the laboratory cleaning machine. Use each glass filter crucible for a maximum of 10 analyses, as the pores become blocked and cannot be cleaned to a sufficient standard after repeated use.

5.2 Drying oven, capable of being maintained at (103 ± 2) °C.

5.3 Desiccator, with silica gel.

5.4 Glass beaker, of capacity 150 ml, tall form.

5.5 Filtering bottle.

5.6 Vacuum pump (for the filtration).

5.7 Analytical balance.

5.8 Measuring cylinder, of capacity 50 ml.

5.9 Glass rods of different sizes.

6 Sampling

6.1 General

A representative sample should have been sent to the laboratory. It should not have been damaged or changed during transport or storage.

Sampling is not part of the method specified in this International Standard. A recommended sampling method is given in ISO 5555^[2].

6.2 Preparation of the test sample

Heat the test sample to max. 60 °C, avoiding local overheating, and homogenize by powerful stirring. Record any specific treatments of the test sample (filtration, melting, etc.) in the test report.

1) Duran® filter crucible, porosity 3, diameter 36 mm, is an example of a suitable product available commercially. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by ISO of this product.

2) Extran® MA03 phosphate-free is an example of a suitable product available commercially. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by ISO of this product.

7 Procedure

7.1 Dry the glass filter crucible for 1 h at 103 °C in the drying oven (5.2), allow to cool to room temperature in the desiccator (5.3) and weigh (5.7) to the nearest 0,1 mg.

7.2 From the test sample (6.2), accurately weigh (5.7) a test portion of approximately 10,00 g to the nearest 0,01 g in the beaker (5.4).

If the TIM is much higher than 0,3 % mass fraction, reduce the mass of the test portion, and record the details in the test report.

7.3 Dissolve the test portion in 100 ml of toluene while stirring with a glass rod.

7.4 Filter the solution through the glass filter crucible (5.1). Rinse the beaker twice with 25 ml of toluene each time and filter it just as before through the glass filter crucible.

7.5 Dry the filter crucible at 103 °C in the drying oven (5.2) for 2 h, allow to cool to room temperature in the desiccator (5.3) and then weigh (5.7) to the nearest 0,1 mg.

CAUTION — To avoid exposure to toluene, allow the toluene to evaporate at ambient temperature under local exhaust ventilation before transferring the crucible to the drying oven or use a drying oven in fume hood.

7.6 Then place the filter crucible in the drying oven (5.2) for 30 min, allow to cool to room temperature in the desiccator (5.3) and weigh (5.7). The difference in mass from that measured in 7.5 shall not be more than 0,5 mg, otherwise repeat the drying procedure until a constant mass is obtained. If the mass increases, take the lower measured value.

8 Calculation

The toluene insoluble matter content, w_{TIM} , in grams per 100 g, is given by:

$$w_{\text{TIM}} = \frac{m_2 - m_1}{m_0} \times 100$$

where

m_0 is the mass, in grams, of the test portion;

m_1 is the mass, in grams, of the crucible (7.1);

m_2 is the mass, in grams, of the crucible plus the residue (7.5).

Report the result to two decimal places.

9 Precision

9.1 Interlaboratory test

Details of interlaboratory tests on the precision of the method are summarized in Annex A. The values derived from this interlaboratory test may not be applicable to concentration ranges and matrices other than those given.

9.2 Repeatability

The absolute difference between two independent single test results, obtained with the same method on identical test material in the same laboratory by the same operator using the same equipment within a short interval of time, shall in not more than 5 % of cases exceed the values of r given in Tables A.1 and A.2.

9.3 Reproducibility

The absolute difference between two single test results, obtained with the same method on identical test material in different laboratories by different operators using different equipment, shall in not more than 5 % of cases exceed the values of R given in Tables A.1 and A.2.

10 Test report

The test report shall contain at least the following information:

- a) the test result(s) obtained;
- b) the test method used, together with reference to this International Standard;
- c) all the information required for the complete identification of the sample;
- d) the sampling method used, if known;
- e) all operating details not specified in this International Standard, or regarded as optional, together with details of any incident that may have influenced the result(s).

Annex A (informative)

Results of interlaboratory tests

The precision of the method is the result of two interlaboratory studies organized by the Joint Committee for the Analysis of Fats, Oils, Fat Products, Related Products and Raw Materials (GA Fett) and the International Lecithin and Phospholipid Society (ILPS). The studies were carried out in 1997 and 2007 on three and six samples, respectively. The test in 2007 was carried out with two glass filter crucibles with two different pore sizes (P 40 and P 100). The results for glass filter crucible P 40, evaluated according to ISO 5725-1^[3] and ISO 5725-2^[4], are given in Tables A.1 and A.2.

Table A.1 — Summary of 1997 statistical results (glass filter crucible P 40)

Crude lecithin sample No.	1	2	3
Number of participating laboratories, N	7	7	6
Number of laboratories retained after eliminating outliers, n	7	7	6
Number of individual test results of all laboratories on each sample, n_z	14	14	12
Mean, $\bar{w}_{TIM}$, g/100 g	0,290	0,140	0,430
Repeatability standard deviation, s_r , mg/100 g	0,020	0,020	0,020
Repeatability coefficient of variation, $CV(r)$, %	8,4	16,5	4,4
Repeatability limit, r , g/100 g	0,070	0,070	0,050
Reproducibility standard deviation, s_R , mg/100 g	0,150	0,090	0,100
Reproducibility coefficient of variation, $CV(R)$, %	50,8	63,4	22,7
Reproducibility limit, R , g/100 g	0,410	0,250	0,270

Table A.2 — Summary of 2007 statistical results (glass filter crucible P 40)

Crude lecithin sample No.	1	2	3	4	5	6
Number of participating laboratories, N	14	14	12	14	14	13
Number of laboratories retained after eliminating outliers, n	13	11	11	13	11	10
Number of individual test results of all laboratories on each sample, n_z	26	22	22	26	22	20
Mean, $\bar{w}_{TIM}$, g/100 g	0,051	0,027	0,371	0,060	0,062	0,025
Repeatability standard deviation, s_r , mg/100 g	0,007	0,004	0,057	0,0	0,012	0,007
Repeatability coefficient of variation, $CV(r)$, %	13,4	13,8	15,5	20,8	19,5	27,4
Repeatability limit, r , g/100 g	0,019	0,010	0,161	0,035	0,034	0,019
Reproducibility standard deviation, s_R , mg/100 g	0,034	0,025	0,163	0,044	0,026	0,021
Reproducibility coefficient of variation, $CV(R)$, %	66,5	94,6	43,8	73,1	41,8	86,3
Reproducibility limit, R , g/100 g	0,095	0,071	0,455	0,124	0,072	0,059

A further filter crucible P 100 (G2) with a pore size of 40 µm to 100 µm was tested in the second interlaboratory study. These results, evaluated according to ISO 5725-1^[3] and ISO 5725-2^[4] are given in Table A.3. Due to the wider pore size, the results are much lower and insufficient. Therefore a P 100 filter crucible is not recommended for use for the determination of TIM (see Clause 3, paragraph 2).

Table A.3 — Summary of 2007 statistical results (glass filter crucible P 100)

Crude lecithin sample No.	1	2	3	4	5	6
Number of participating laboratories, N	14	13	14	14	14	13
Number of laboratories retained after eliminating outliers, n	11	12	14	9	12	10
Number of individual test results of all laboratories on each sample, n_z	22	24	28	18	24	20
Mean, $\bar{w}_{TIM}$, g/100 g	0,012	0,008	0,165	0,010	0,016	0,009
Repeatability standard deviation, s_r , mg/100 g	0,004	0,003	0,025	0,0	0,005	0,000
Repeatability coefficient of variation, $CV(r)$, %	36,1	34,6	15,2	0,00	28,1	0,0
Repeatability limit, r , g/100 g	0,012	0,008	0,070	0,000	0,013	0,000
Reproducibility standard deviation, s_R , mg/100 g	0,010	0,011	0,087	0,007	0,013	0,009
Reproducibility coefficient of variation, $CV(R)$, %	82,7	128,6	52,8	70,7	82,4	97,3
Reproducibility limit, R , g/100 g	0,027	0,030	0,244	0,020	0,037	0,025

Bibliography

- [1] ISO 4793, *Laboratory sintered (fritted) filters — Porosity grading, classification and designation*
- [2] ISO 5555, *Animal and vegetable fats and oils — Sampling*
- [3] ISO 5725-1, *Accuracy (trueness and precision) of measurement methods and results — Part 1: General principles and definitions*
- [4] ISO 5725-2, *Accuracy (trueness and precision) of measurement methods and results — Part 2: Basic method for the determination of repeatability and reproducibility of a standard measurement method*
- [5] JECFA, *Lecithin*. Available (2009-06-18) at <http://www.fao.org/ag/agn/jecfa-additives/specs/monograph4/additive-250-m4.pdf>



Organization and Objectives

The Ethiopian Standards Agency (ESA) is the national standards body of Ethiopia established in 2010 based on regulation No. 193/2010. ESA is established due to the restructuring of Quality and Standards Authority of Ethiopia (QSAE) which was established in 1970.

ESA's objectives are:-

- ❖ Develop Ethiopian standards and establish a system that enable to check weather goods and services are in compliance with the required standards,
- ❖ Facilitate the country's technology transfer through the use of standards,
- ❖ Develop national standards for local products and services so as to make them competitive in the international market.

Ethiopian Standards

The Ethiopian Standards are developed by national technical committees which are composed of different stakeholders consisting of educational Institutions, research institutes, government organizations, certification, inspection, and testing organizations, regulatory bodies, consumer association etc. The requirements and/or recommendations contained in Ethiopian Standards are consensus based that reflects the interest of the TC representatives and also of comments received from the public and other sources. Ethiopian Standards are approved by the National Standardization Council and are kept under continuous review after publication and updated regularly to take account of latest scientific and technological changes.

Orders for all Ethiopian Standards, International Standard and ASTM standards, including electronic versions, should be addressed to the Documentation and Publication Team at the Head office and Branch (Liaisons) offices. A catalogue of Ethiopian Standards is also available freely and can be accessed in from our website.

ESA has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of ESA.

International Involvement

ESA, representing Ethiopia, is a member of the International Organization for Standardization (ISO), and Codex Alimentarius Commission (CODEX). It also maintains close working relations with the international Electro-technical Commission (IEC) and American Society for Testing and Materials (ASTM). It is a founding member of the African Regional Organization for standardization (ARSO).

More Information?

Contact us at the following address.

The Head Office of ESA is at Addis Ababa.

☎ 011- 646 06 85, 011- 646 05 65

☎ 011-646 08 80

✉ 2310 Addis Ababa, Ethiopia

E-mail: info@ethiostandards.org,

Website: www.ethiostandards.org



Standard Mark